

The present invention relates to a gear wheel construction.

More specifically, the present invention relates to a gear wheel construction which can be used in a precision conveyor device including an apron driven by a timing belt.

More specifically, the gear wheel construction according to the invention can be used, in particular, in a conveyor device in which the timing belt slides on a frame, according to at least a top flat path, driven by driving rollers, and being entrained about two end pulleys, at the end portions of its driving path.

At an intermediate region of the top flat driving path, the gear wheel, or toothed pulley, according to the invention, is arranged at a bottom between a pair of flat pulleys which, by cooperating with the subject gear wheel, cause the timing belt to follow a downward directed loop.

The gear wheel is driven by a driving means including, depending on requirements, a step by step motor, a D.C. motor, a brushless motor, the driving means being coupled to the timing belt through a

geared unit.

As is known, the apron or conveyor belt devices used in precision processing operations, such as to convey workpiece to a machining tool, must be able of locating the workpiece in a very accurate manner, with respect to the machining tool.

A problem affecting the above disclosed system is that of the wear of the teeth of the gear wheel, with a consequent backlash between the gear wheel and timing belt, which negatively affect the movement precision of the timing belt and apron.

SUMMARY OF THE INVENTION

Accordingly, the aim of the present invention is to provide an improved gear wheel construction, which is suitable to overcome the above disclosed drawback.

Within the scope of the above mentioned aim, a main object of the present invention is to provide such a gear wheel which is very simple construction-wise and very reliable in operation.

Another object of the present invention is to provide such a gear wheel construction allowing to recover the backlash due to the wear of the gear wheel teeth, and this by a simple and quick adjusting

09876454 060701
102090 19192560

operation.

According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by a gear wheel construction, characterized in that said gear wheel construction comprises a first gear wheel portion, including first half-teeth, which can be coupled to a second gear wheel portion, including second half-teeth, by adjustable coupling means, thereby said first and second half-teeth form by pairs teeth of said gear wheel, said second gear wheel portion being suitable to turn about said first gear wheel portion, about a rotary axis of said gear wheel, and being locked by said coupling means so as to change the distance of the first and second half teeth in each said pair.

BRIEF DESCRIPTION OF THE DRAWINGS

Further characteristics and advantages of the present invention will become more apparent hereinafter from the following detailed disclosure of a preferred, though not exclusive, embodiment of the invention, which is illustrated, by way of a merely indicative, but not limitative, example in the

driving path, is arranged the gear wheel or toothed pulley according to the invention, which, in particular, is located at the bottom between a pair of flat pulleys which, by cooperating with the subject gear wheel, cause the timing belt to follow or define a downward directed loop.

In particular, the gear wheel is driven by driving means including, depending on requirements, a step by step motor, a D.C. motor, or a brushless motor, through a suitable geared unit.

The gear wheel construction 1 according to the invention comprises a first gear wheel portion 2 including first half-teeth 4, which can be coupled to a second gear wheel portion 3, including second half-teeth 5, through adjustable coupling means, comprising, for examples, screws 6 for engagement in corresponding threaded seats or recesses 7 formed in the first gear wheel portion 2 and passing through enlarged recesses 8 formed in the second gear wheel portion 3.

The gear wheel portions 2 and 3 can be coupled by their mutual facing surfaces.

Of the latter, only the surface 9 of the first gear wheel portion can be seen in the figures,

09876451 060701
102990 1949360

with respect to the first gear wheel portion 2, by simply clamping the screws 6.

It has been found that the invention fully achieves the intended aim and objects.

In fact a gear wheel construction has been provided, which has been specifically designed for application to a conveyor device for use in automatized machining lines, or in individual machines, requiring several precision locating operations on a plurality of workpieces to be machined.

In practicing the invention, the used materials, and the size thereof, can be any, according to requirements and the status of the art.